

Product description:

For 20 years LEDStripe® has added lighting elegance and distinction to buildings worldwide. This patented LED-based rigid tubing system, with its large profile and long runs, has become the border tube system of choice for many retail, restaurant, and lodging chains.

Product data:

SloanLED Manufacturer -

Product name -SloanLED LEDStripe

Factory bends - 305 mm (12 in) radius (radial and flat bend)

Radial bend 4.25m (14 ft) In-field bends -Flat bend 5.8m (19 ft)

Operating temperature --40° C to + 70° C

Colours -Red, Orange, Amber, True Yellow, Green, Blue, White (6500k), Lemon Yellow

Unlit product colour chart:

Red	Orange	Amber	True Yellow
PANTONE 1797 C	PANTONE 1665 C	PANTONE 2012 C	PANTONE 7405 C
Green	Blue	Lemon Yellow	
PANTONE 355 C	PANTONE 2935 C	PANTONE 138 C	











- Daytime color when non-illuminated
- High impact acrylic: UV stable, hydrocarbon insensitive, and non-fading
- Can be factory bent to minimum 12-inch radius
- · Can be cut in the field
- Conforms to UL 48 requirements

Dimensions L x W x H -

Width	25mm (1.00 in)
Height	43mm (1.68in)
Lengths	0.3m (1 ft); 0.6m (2 ft)
	1.2m (4 ft); 1.8m (6 ft)
	2.4m (8 ft): 3.0m (10 ft)

IP66 Protection class -

MacAdam Step 3 **Binning** -

5.0 W/1.5 W (except 0.3m (1 ft) Power per meter/foot piece at 3.0 W on average

18.3 m (60 ft) per SloanLED 100 W 24 Power capacity -VDC power supply

Color	Lumens per m/ft
Red	71.98 / 21.94
Orange	19.52 / 5.95
Amber	32.28 / 9.84
True Yellow	275.59 / 84.00
Green	65.35 / 19.92
Blue	31.50 / 9.60
White (6500 K)	387.40 / 118.08
Lemon Yellow	32.28 / 9.84
Lemon Yellow	32.28 / 9.84













SLOANLED LEDSTRIPE





Color	Part number	Color	Part number
Red	701189- X H	Green	701189D-G- X
Orange	701189-A- X D	Blue	701189A-B- X D
Amber	701189-Y- X D	White	701189E-W- X
True Yellow	701189-YT- X	Lemon Yellow [§]	701189E-WY- X

- # "X" in part number denotes length (0.3-m [1-ft]*; 0.6-m [2-ft]; 1.2-m [4-ft]; 1.8-m [6-ft]; 2.4-m [8-ft]; or 3.0-m [10-ft])
- § Lemon Yellow illuminates lighter than its daytime color. Lemon Yellow daytime color is Amber.

Item description	Approx. cut increments	Actual length
0.3-m (1-ft) Tube*	25 mm (1 in)	33.0 cm (13.0 in)
0.6-m (2-ft) Tube		63.5 cm (25.0 in)
1.2-m (4-ft) Tube		124.5 cm (49.0 in)
1.8-m (6-ft) Tube	75 mm (3 in)	186.7 cm (73.5 in)
2.4-m (8-ft) Tube		247.7 cm (97.5 in)
3.0-m (10-ft) Tube		308.6 cm (121.5 in)

24 VDC power supply	LEDStripe 24 VDC, all colors ¹
30 W power supply	5.5 m / 18 ft
60 W power supply	11 m / 36 ft
96 W power supply	Two legs 9.04 m (30 ft) each⁴
3 x 96 W power supply	3 x two legs 9.04 m (30 ft) each [∆]
100 W power supply	Two legs 9.04 m (30 ft) each [∆]
150 W power supply	Three legs 9.04 m (30 ft) each∆
Watts per assembly	5 W per m (1.5 W per ft)

- ¶ Footages expressed are total (maximum 9 m [30 ft] per leg). Power Output is based on Power Supply loading of two parallel 9 m (30 ft) legs. Actual power draw may depend on loading configuration.
- Δ If more than two parallel legs are used, check output voltage and current of power supply: Current \leq 4.0 A, Voltage \geq 23.3 VDC.











sales@applelec.co.uk











SLOANLED LEDSTRIPE





Accessory	Part number	Description	
Joint and corner covers			
701361-X	701362-X	701363-X 701364-X	
Joint cover	701361-X		
Outside corner	701362-X	T.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
Inside corner	701363-X	"X" in part number denotes color	
Step corner	701364-X		
Cables and connectors			
701158-120 & 701158-180 7013	85 7	701160-3 701187-DC 701188-DC	
Hook-up cable, 3.0-m (10-ft)	701158-120	Connects LEDStripe to power supply	
Hook-up cable, 4.6-m (15-ft)	701158-180		
Jumper kit	701385	For routing around field-cut sections	
Y connector	701160-3	Three-way connector for joining two sections to one	
Wiring pigtail, large connector	701187-DC	Male, outdoor-rated connector	
Wiring pigtail, small connector	701188-DC	Female, outdoor-rated connector	
Mounting			
400775	701156	400828-FC 701491	
Mounting button	701156	Circular button for standard installation	
Mounting clip	400775	Square clip with flanged end	
Acrylic end cap	400828-FC	For adjusting product length	
Field end cap installation kit	701491	Glue, PCB sealer, de-burr sandpaper, instructions	



















